

PATENT  
450100-03206**IN THE CLAIMS:**

Please replace the claims now on file with the following listing of the claims. This claim listing replaces and supersedes all prior listings of the claims.

Cancel claim 1.

2. (Currently Amended) A The data transmission device ~~according to claim 1~~  
comprising:

an input means for receiving as input a first packet containing header information and real time data, the header information including at least synchronizing time reference information necessary for producing a synchronizing signal to be used by the receiving side;

an extraction means for extracting the synchronizing time reference information from the first packet received by said input means;

a conversion means for converting the synchronizing time reference information extracted by said extraction means into a time stamp;

a packet formation means for forming a second packet containing the header information including the time stamp obtained by the conversion of said conversion means and the first packet received by said input means; and

a transmission means for transmitting the second packet formed by said packet formation means

wherein said input means receives as input the first packet formatted to the MPEG2-TS format;

said extraction means extracts a PCR (Program Clock Reference) contained in the first packet; and

PATENT  
450100-03206

said conversion means converts the extracted PCR into the time stamp conforming to the RTP (Real-time Transport Protocol) so as to make it to be contained in the second packet.

3. (Currently Amended) The data transmission device according to claim [[1]] 2, wherein said conversion means copies part of said synchronizing time reference information to produce said time stamp.

4. (Currently Amended) The data transmission device according to claim [[1]] 2, wherein said conversion means adds an offset to said synchronizing time reference information to produce said time stamp.

Cancel Claim 5.

6. (Currently Amended) A The data transmission method ~~according to claim 5,~~  
comprising the steps of:

receiving as input a first packet containing header information and real time data, the header information including at least synchronizing time reference information necessary for producing a synchronizing signal to be used by a receiving side;

extracting the synchronizing time reference information from said first packet received;  
converting said extracted synchronizing time reference information into a time stamp;

forming a second packet containing said header information and the first packet, the header information including said time stamp and transmitting said second packet,

wherein the first packet that is received is formatted to the MPEG2-TS format;

PATENT  
450100-03206

the synchronizing time reference information that is extracted from the first packet is PCR (Program Clock Reference); and

further comprising the step of converting the extracted PCR into a time stamp conforming to the RTP (Real-time Transport Protocol) to be contained in the second packet.

7. (Currently Amended) The data transmission method according to claim [[5]] 6, wherein part of said synchronizing time reference information is copied to produce said time stamp.

8. (Currently Amended) The data transmission method according to claim [[5]] 6, wherein an offset is added to said synchronizing time reference information to produce said time stamp.